



Red Top Drilling Co., Inc.

Office: Hot Springs Boulevard
P. O. Box 505
Las Vegas, New Mexico 87701

Phone: (505) 425-8371



Owner Lloyd, Gary Permit No. CR-2490

Location of Well 2 miles before Chacon

Date Started 8/25/94 Date Completed 8/25/94

Driller Roger Isbell TOTAL DEPTH 101 Ft.

Water bearing stratas: Casing 5" PVC

G.P.M. 17 From 21 ft. to 22 ft. From 1 1/2 ft. to 6.4 ft.

G.P.M. Seep From 96 ft. to 96 1/2 ft. Casing

G.P.M. From ft. to ft. From ft. to ft.

G.P.M. From ft. to ft. Perforation:

Total G.P.M. 17 Type Test Air From 20 to 24 ft.

Static Water level from surface 19' 6" ft. From to ft.

Packer set @ NON Ft. Hole size 1 1/2 to 2 1/4 ft. From to ft.

Hole size 6-3/4 10 ft. From to ft.

Remarks Hit sulphur water at 96', back filled with cuttings and cement to 80'.

WELL LOG

Thickness of strata	Formation & Color	To a depth of
..... ft. ft.
..... ft.	Pea gravel from 24-16' ft.
..... ft.	Bentonite pellets and ft.
..... ft.	cement on top of pea ft.
..... ft.	gravel. ft.
..... ft. ft.
3 ft.	Brown Top Soil	3 ft.
8 ft.	Brown Sand Gravel & Clay	11 ft.
2 ft.	Gray Boulders	13 ft.
9 ft.	Brown Shale & Gravel	22 ft.
52 ft.	Black Shale	74 ft.
1 ft.	Gray Limestone	75 ft.
21 ft.	Black Shale	96 ft.
1/2 ft.	Gray Sandstone	96 1/2 ft.
4 1/2 ft.	Black Shale	101 ft.
..... ft. ft.
..... ft. ft.
..... ft. ft.

WATER ANALYSIS

Ph 7.5 Iron 0 Hardness 28